

Cutting layout

The fabric is folded selvedge to selvedge, so the usable width is HALF the bolt. A piece marked "ON FOLD" sits on that fold.


PURCHASE SEPARATELY: 1 x 804 mm double-fold bias binding, 5 mm finished width, for neck. Not included in cloth yardage.

PURCHASE SEPARATELY: 2 x 468 mm double-fold bias binding, 5 mm finished width, for armhole. Not included in cloth yardage.

PURCHASE SEPARATELY: 6 x 32 mm buttons. Not included in cloth yardage.

PURCHASE SEPARATELY: lightweight fusible interfacing for the two front facings, 2 x 139 mm wide x 746 mm long (sewing guide section 3b). Not included in cloth yardage.


115 cm wide fabric - layout uses 1.69 m



scale 1:27 . dashed line on the left = the fold . usable width 575 mm

#2 BACK: ON FOLD . #1 FRONT: 2 MIRRORED . #3 SLEEVE: 2 MIRRORED

150 cm wide fabric - layout uses 1.69 m



scale 1:27 . dashed line on the left = the fold . usable width 750 mm

#2 BACK: ON FOLD . #1 FRONT: 2 MIRRORED . #3 SLEEVE: 2 MIRRORED

Yardage covers these placements only; shrinkage and matching prints need extra cloth. Keep each grainline parallel to the selvedge. Cut single pieces through the top layer only. CHECKED FABRIC: the layout above is drawn folded for plain fabric. Cut checks single layer, right side up (sewing guide, section 1): open the fabric, lay each piece as drawn and again flipped for its mirrored copy, and add about 0.5 m to the length above to match the checks.